

COIR LOGS

PREMIUM BIODEGRADABLE

Ferguson Coir Logs are sediment retention fiber rolls used to help minimize accelerated erosion in shoreline, stream channel, and other applications. Coir Logs are made from 100% coconut coir fiber bound by a high strength netting in multiple lengths and diameters. Premium Coir Logs are recommended for low energy site usage such as lakes, streambanks, bayshores, and other concentrated flow areas.

SPECIFICATIONS

MATERIAL CONTENT

Fiber Fill	100% Natural Coconut Fiber
Netting	Biodegradable Coir Twine
Openings	2" x 2" Mesh

TYPICAL VALUES

Nominal Diameter	12", 16", 20"
Nomical Length	10', 12', 20'
Unit Weight	7.0 lbs/ft (12"), 12.5 lbs/ft (16"), 19.5 lbs/ft (20")
Density	9.0 lbs/cu.ft
Water Velocity	8 ft/sec (12"), 12 ft/sec (16"), 15.2 ft/sec (20")
Longevity	2-5 years



Disclaimer: The information presented herein is, to the best of our knowledge, true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe on any patent.

For more information about Erosion and Sediment Control, contact Inside Sales at **800.448.3636** or **info@ferguson.com** or visit us at **fergusonwaterworks.com**