



SiltSoxx Original Product Specs:

Netting Material Type	Original Pallet Netting Heavy Duty Multi-Filament Polypropylene (MFPP)		
Netting Degradation	Photodegradable		
Netting Diameters	5", 8", 12", 18", 24"		
Netting Opening Size	1/8"		
Netting Color	Green w/ Thin Black Stripe		
Fabric Tensile Strength (ASTM D4595) ¹	546 lbs		
Fill Type	Tested & Certified, Locally Sourced Composted FilterMedia		
Functional Longevity ²	up to 5 years		
Edging Material	Edging Media Bags Available		
Staking Recommendation	Every 10-ft (stakes not included on precuts)		



Netting Sample



Fill Sample

ORIGINAL Item List:

Part Number	Diameter	Total Linear Feet per pallet	Unit Length	Units per pallet	Stakes per pallet	Pallet Weight
P05-400S2	5-in	400-ft	200	2	42	~ 1600 lbs
PN05-400S16	5-in	400-ft	25-ft	16	0	~ 1600 lbs
P08-200	8-in	200-ft	200-ft	1	21	~ 1600 lbs
PN08-200S20	8-in	200-ft	10-ft	20	0	~ 1600 lbs
PN08-200S10	8-in	200-ft	20-ft	10	0	~ 1600 lbs
P12-110	12-in	110-ft	110-ft	1	12	~ 1700 lbs
PN12-100S10	12-in	100-ft	10-ft	10	0	~ 1650 lbs
P18-55	18-in	55-ft	55-ft	1	7	~ 1750 lbs
PN18-50S5	18-in	50-ft	10-ft	5	0	~ 1650 lbs
P24-30	24-in	30-ft	30-ft	1	4	~ 1800 lbs

Shipping Specs:

Pallets per TL	26	
Shipping Dimensions	40L x 48W x 66H	
Packaging	40 x 48 Pallet with Plastic Stretch-Wrap or Super Sack	
Storage Life	Under Roof - 6 months / Outdoors - 3 months	

Diameter	Stake Size (Nominal)
5-in	1" x 1" x 12"
8-in	2" x 2" x 24"
12-in	2" x 2" x 24"
18-in	2" x 2" x 36"
24-in	2" x 2" x 42"



¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods. ²Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.